

Bezeichnung	Bohr- Ø	Klemmstärke Standard	Verankerung Standard	Klemmstärke Mindest	Verankerung Mindest	Klemmstärke Max.	Verankerung Max.	Setztiefe h ₁	Dübellänge	Gewinde	SW	Drehmoment
B 8-4/60	8 mm	–	–	4 mm	35 mm	–	–	hef + 12 mm	60 mm	M8×25	13 mm	15 Nm
B 8-10- 19/75	8 mm	10 mm	44 mm	19 mm	35 mm	–	–	hef + 12 mm	75 mm	M8×40	13 mm	15 Nm
B 8-15- 24/80	8 mm	15 mm	44 mm	24 mm	35 mm	–	–	hef + 12 mm	80 mm	M8×45	13 mm	15 Nm
B 8-20- 29/85	8 mm	20 mm	44 mm	29 mm	35 mm	–	–	hef + 12 mm	85 mm	M8×50	13 mm	15 Nm
B 8-25- 34/90	8 mm	25 mm	44 mm	34 mm	35 mm	–	–	hef + 12 mm	90 mm	M8×55	13 mm	15 Nm
B 8-30- 39/95	8 mm	30 mm	44 mm	39 mm	35 mm	4 mm	70 mm	hef + 12 mm	95 mm	M8×60	13 mm	15 Nm
B 8-35- 44/100	8 mm	35 mm	44 mm	44 mm	35 mm	9 mm	70 mm	hef + 12 mm	100 mm	M8×65	13 mm	15 Nm
B 8-45- 54/110	8 mm	45 mm	44 mm	54 mm	35 mm	19 mm	70 mm	hef + 12 mm	110 mm	M8×75	13 mm	15 Nm
B 8-55- 64/120	8 mm	55 mm	44 mm	64 mm	35 mm	29 mm	70 mm	hef + 12 mm	120 mm	M8×85	13 mm	15 Nm
B 8-100- 109/165	8 mm	100 mm	44 mm	109 mm	35 mm	74 mm	70 mm	hef + 12 mm	165 mm	M8×85	13 mm	15 Nm
B 10-10- 16/85	10 mm	10 mm	48 mm	16 mm	42 mm	–	–	hef + 14 mm	85 mm	M10×40	17 mm	30 Nm
B 10-15- 21/90	10 mm	15 mm	48 mm	21 mm	42 mm	–	–	hef + 14 mm	90 mm	M10×45	17 mm	30 Nm
B 10-20- 26/95	10 mm	20 mm	48 mm	26 mm	42 mm	–	–	hef + 14 mm	95 mm	M10×50	17 mm	30 Nm
B 10-30- 36/105	10 mm	30 mm	48 mm	36 mm	42 mm	–	–	hef + 14 mm	105 mm	M10×60	17 mm	30 Nm
B 10-45- 51/120	10 mm	45 mm	48 mm	51 mm	42 mm	13 mm	80 mm	hef + 14 mm	120 mm	M10×75	17 mm	30 Nm

Bezeichnung	Bohr- Ø	Klemmstärke Standard	Verankerung Standard	Klemmstärke Mindest	Verankerung Mindest	Klemmstärke Max.	Verankerung Max.	Setztiefe h ₁	Dübellänge	Gewinde	SW	Drehmoment
B 10-50-56/125	10 mm	50 mm	48 mm	56 mm	42 mm	18 mm	80 mm	hef + 14 mm	125 mm	M10×80	17 mm	30 Nm
B 10-100-106/175	10 mm	100 mm	48 mm	106 mm	42 mm	68 mm	80 mm	hef + 14 mm	175 mm	M10×80	17 mm	30 Nm
B 10-140-146/215	10 mm	140 mm	48 mm	146 mm	42 mm	108 mm	80 mm	hef + 14 mm	215 mm	M10×80	17 mm	30 Nm
B 12-13/95	12 mm	–	–	13 mm	50 mm	–	–	hef + 17 mm	95 mm	M12×50	19 mm	50 Nm
B 12-10-25/105	12 mm	10 mm	65 mm	25 mm	50 mm	–	–	hef + 17 mm	105 mm	M12×60	19 mm	50 Nm
B 12-15-30/110	12 mm	15 mm	65 mm	30 mm	50 mm	–	–	hef + 17 mm	110 mm	M12×65	19 mm	50 Nm
B 12-20-35/115	12 mm	20 mm	65 mm	35 mm	50 mm	–	–	hef + 17 mm	115 mm	M12×70	19 mm	50 Nm
B 12-30-45/125	12 mm	30 mm	65 mm	45 mm	50 mm	–	–	hef + 17 mm	125 mm	M12×80	19 mm	50 Nm
B 12-50-65/145	12 mm	50 mm	65 mm	65 mm	50 mm	15 mm	100 mm	hef + 17 mm	145 mm	M12×100	19 mm	50 Nm
B 12-65-80/160	12 mm	65 mm	65 mm	80 mm	50 mm	30 mm	100 mm	hef + 17 mm	160 mm	M12×100	19 mm	50 Nm
B 12-85-100/180	12 mm	85 mm	65 mm	100 mm	50 mm	50 mm	100 mm	hef + 17 mm	180 mm	M12×100	19 mm	50 Nm
B 12-105-120/200	12 mm	105 mm	65 mm	120 mm	50 mm	70 mm	100 mm	hef + 17 mm	200 mm	M12×100	19 mm	50 Nm
B 12-125-140/220	12 mm	125 mm	65 mm	140 mm	50 mm	90 mm	100 mm	hef + 17 mm	220 mm	M12×80	19 mm	50 Nm
B 12-145-160/240	12 mm	145 mm	65 mm	160 mm	50 mm	110 mm	100 mm	hef + 17 mm	240 mm	M12×80	19 mm	50 Nm
B 12-160-175/255	12 mm	160 mm	65 mm	175 mm	50 mm	125 mm	100 mm	hef + 17 mm	255 mm	M12×80	19 mm	50 Nm
B 12-190-205/285	12 mm	190 mm	65 mm	205 mm	50 mm	155 mm	100 mm	hef + 17 mm	285 mm	M12×80	19 mm	50 Nm
B 12-230-245/325	12 mm	230 mm	65 mm	245 mm	50 mm	195 mm	100 mm	hef + 17 mm	325 mm	M12×80	19 mm	50 Nm

Bezeichnung	Bohr- Ø	Klemmstärke Standard	Verankerung Standard	Klemmstärke Mindest	Verankerung Mindest	Klemmstärke Max.	Verankerung Max.	Setztiefe h ₁	Dübellänge	Gewinde	SW	Drehmoment
B 12-260-275/355	12 mm	260 mm	65 mm	275 mm	50 mm	225 mm	100 mm	hef + 17 mm	355 mm	M12×80	19 mm	50 Nm
B 16-13/115	16 mm	–	–	13 mm	64 mm	–	–	hef + 20 mm	115 mm	M16×60	24 mm	100 Nm
B 16-10-28/130	16 mm	10 mm	82 mm	28 mm	64 mm	–	–	hef + 20 mm	130 mm	M16×70	24 mm	100 Nm
B 16-30-48/150	16 mm	30 mm	82 mm	48 mm	64 mm	–	–	hef + 20 mm	150 mm	M16×90	24 mm	100 Nm
B 16-60-78/180	16 mm	60 mm	82 mm	78 mm	64 mm	22 mm	120 mm	hef + 20 mm	180 mm	M16×110	24 mm	100 Nm
B 16-80-98/200	16 mm	80 mm	82 mm	98 mm	64 mm	42 mm	120 mm	hef + 20 mm	200 mm	M16×110	24 mm	100 Nm
B 16-100-118/220	16 mm	100 mm	82 mm	118 mm	64 mm	62 mm	120 mm	hef + 20 mm	220 mm	M16×80	24 mm	100 Nm
B 16-130-148/250	16 mm	130 mm	82 mm	148 mm	64 mm	92 mm	120 mm	hef + 20 mm	250 mm	M16×80	24 mm	100 Nm
B 16-165-183/285	16 mm	165 mm	82 mm	183 mm	64 mm	127 mm	120 mm	hef + 20 mm	285 mm	M16×80	24 mm	100 Nm
B 16-200-218/320	16 mm	200 mm	82 mm	218 mm	64 mm	162 mm	120 mm	hef + 20 mm	320 mm	M16×80	24 mm	100 Nm

